

PET OR IODINE AIR MONITOR GAS AND PARTICULATE MODEL # FM-7-ABNI

FEATURES:

- INTEGRATED EXPOSURE
- HIGH SENSITIVITY
- REAL TIME ALARM
- LINE OPERATED
- PORTABLE
- STANDARD FM-7/9 MODULES
- CAN DRAW AIR FROM HOOD, DUCT, ETC.
- QUICK CHANGE FILTER CARTRIDGE
- REGULATED AIR FLOW
- RS232 COMPUTER INTERFACE
- OPTIONAL DATA LOGGER



APPLICATION: The **FM-7-ABNI** Air Monitors assure safety against airborne radioactivity contamination by means of constant check with alarm and record capability. It provides integrated exposure information and can provide hard copy via external printer or computer. It is a complete system but may be expanded per need with modules of the **FM-7** series. The **FM-7-ABNI** are the **more sensitive and versatile version** of the broadly used long time standard, the FM-5-ABNI. They may be used to monitor stack effluent down to EPA levels as well as hoods, glove box or workplace air.

DESCRIPTION: The **FM-7-ABNI** uses a standard charcoal filter in TA's unique quick change, no leak holder to trap any airborne Radio Iodine. The filter is under constant surveillance via a thin window scintillation detector. Air is drawn by a regulated pump through a three-foot inlet hose and exhausted via a flow meter through another three-foot hose. These may be extended to allow monitoring of hoods, glove boxes, stacks, etc. Time is recorded by an odometer type timer wired into the pump circuit. The unit is completely self-contained and portable. Complete with 10 filter cartridges.

SPECIFICATIONS

- Sensitivity:** Limit of sensitivity and (as Iodine 131 or positron) at 150 liters/minute air flow rate is 4×10^{-13} $\mu\text{Ci/cc}$ integrated over an 8 hour period, or 8×10^{-14} $\mu\text{Ci/cc}$ for a 40 hour period. This corresponds to 2×10^{-10} $\mu\text{Ci/ml}$ minute exposure which is equal to 0.6% of the California Safety Code Title 17 and USNRC Title 10 limit for 40 hour weekly exposure to most hazardous beta and/or gamma emitter in absence of Ac 227.
- Detector:** 2" diameter probe with thin window, thin crystal, scintillation detector, Model PGS-3I for sensitivity to all iodines.
- Electronic Modules Include:]** MVR-5R
- Power and H.V. Bias Supply.**
- FIL-7DP**
- Programmable Scaler.
- MGC-23**
- RS-232 Computer Interface (internal).
- MAC-5**
- Air Control Timer; Low Flow Alarm Flowmeter.
- MGA-5**

TA TECHNICAL ASSOCIATES

7051 ETON AVENUE, CANOGA PARK, CA 91303
TELEPHONE: (818)-883-7043 * FAX: (818) 883-6103
e-mail: tagold@nwc.net * www.tech-associates.com

**PET OR IODINE AIR MONITOR
GAS AND PARTICULATE
MODEL # FM-7-ABNI**

- Single Channel Analyzer**
- WIN-W**
- Optional Data Logger Software**
- Pump:** Muffler and trap included. 115V 60Hz 2A. (230 V 50-60 Hz optional).
- Shielding:** 1" lead about sample and detector.
- Range:** 1×10^{-13} to 1×10^{-7} $\mu\text{Ci/cc}$ or (Ci/m^3) .
- Alarm:** Settable. 2000 Hz beeper and red flasher.
- Response Time:** Settable 1 second to 40 hours.
- Readout:** 6 digit LED for programmed information plus 6 digit LCD for integrated dose.
- Power:** 115V, 50-60 Hz (230 V optional).
- Flow Rate:** Regulated. Normally set at 70 liters/min.
- Filters:** Includes package of 10 silver activated charcoal filter cartridges Model CF-1.
Can also use membrane, paper or glass fiber filters for particulates only.
- Case:** Electronics housed in enameled aluminum carrying case; handles included.
- Dimensions:**

Excluding pump and detector assembly: 17"W x 13"H x 13 1/2" D.
Detector assembly 5"W x 10"H x 6" D.
Pump assembly 8"W x 8"H x 14"D.
- Accessories:** Filter: Free flowing silver activated charcoal disposable cartridge.
- Shipping Weight:** 84lbs.

TA TECHNICAL ASSOCIATES

7051 ETON AVENUE, CANOGA PARK, CA 91303
TELEPHONE: (818)-883-7043 * FAX: (818) 883-6103
e-mail: tagold@nwc.net * www.tech-as-associates.com