

# ANALYZING RATEMETER SCALER

## PORTABLE

### Model - LAM-SCA & LAM-10-DSC

#### FEATURES:

- SINGLE CHANNEL ANALYZER
- VERSATILE AC & RECHARGEABLE BATTERY
- THREE PRESETTABLE WINDOW POSITIONS
- SWITCH SELECTABLE
- SIX DECADES
- CRYSTAL CONTROLLED
- USE WITH ANY T/A GM, PROPORTIONAL, OR SCINTILLATION ALPHA, BETA, GAMMA, X-RAY NEUTRON PROBE
- SPLASH PROOF

#### LAM-10-DSC

- DUAL SINGLE CHANNEL ANALYZER
- 2 INDEPENDENT DETECTOR INPUTS
- COINCIDENCE CIRCUIT SIGNALS IF BOTH DETECTORS SEE A PULSE AT THE SAME TIME



LAM-SCA



LAM-10-DSC

#### DESCRIPTION:

The **LAM-SCA & LAM-10-DSC** are sturdy portable instruments designed for rugged field use.

- Both integrate and ratemeter functions.
- Single channel analyzer with three presettable windows.
- Variable high voltage 0-2000v.
- All closures are gasket sealed to result in a splashproof instrument.
- LCD style scaler readout.

The time base for integrate operation is user settable. The LAM-SCA & LAM-10-DSC accommodate pulses from all types of detectors including scintillators, proportional and GM detectors. Six digits are incorporated into the ratemeter.

Gate times for the integrate mode may be set from 1 to 10,000 seconds. The integrate capability is particularly useful for increasing the accuracy of rate measurements and for operating optional printer.

Power switch and HV pot and other controls are designed to prevent inadvertent change. The audio output of the high level alarm is controlled by a volume mute switch.

Standard features include jack for AC adapter and serial output jack with optional USB adaptor. Yet the overall instrument, including all of these functions and battery life up to 1 week, weighs only 5 pounds.



**TECHNICAL ASSOCIATES**  
**OVERHOFF TECHNOLOGY**

7051 Eton Ave., Canoga Park, CA 91303  
818-883-7043 (Phone) 818-883-6103 (Fax)

[tagold@nwc.net](mailto:tagold@nwc.net)

[WWW.TECH-ASSOCIATES.COM](http://WWW.TECH-ASSOCIATES.COM)

Divisions of



US NUCLEAR CORP

# ANALYZING RATEMETER SCALER

## PORTABLE

### Model - LAM-SCA & LAM-10-DSC

#### SPECIFICATIONS:

- **Digital-Readout:** 6 digit LCD Rate, 8 digit integrate.
- **Time Base:** Crystal controlled 1-10,000 seconds, user settable.
- **Display Modes:** Rate, Integrate.
- **Range:**  
**Usable Probes Cover Range:** 1uR/hr to 1000 R/hr; 0 to 30,000 Cps; 0.1 mRem/hr to 10 Rem/hr.
- **Audio Alarm:** Piezo electric sounder with mute switch.
- **Single Channel:**  
**3 Switch Selectable Windows:** 2 preset (resettable) window positions plus one "variable".
- **Analyzer/Discriminator:** 10-turn, 1000 division pot for each threshold.  
10-turn, 1000 division pot for window width.
- **Detector:**  
**Mates with T/A Probes, any GM, Proportional or Scintillation:** Alpha, Beta, Gamma, Positron, X-Ray, Neutron, Tritium.
- **Detector Connector:** BNC bulkhead mount (MHV optional).
- **Detector Bias:** 0-2000V regulated and filtered.
- **Supply:** High Voltage is adjustable & repeatable with the 10 turn dial.
- **Settable scale factors allow readout in almost any units.**
- **Engineering Units:** User can input correct conversion factor and change to any units.
- **Controls:** Front Panel: On-Off, Alarm-mute, Rate, Integrate, Reset.
- **Calibration:** Digital input of calibration factor gives high precision adjustment.
- **Alarm:** 2000 Hz audio tone with audio "mute" switch + RED LIGHT, high current relay.
- **Serial Output:** Two way, RS-232 standard, USB optional.
- **Construction:** NEMA-4X polycarbonate gasket sealed case with handle:  
Rugged / splash-proof.  
All plug in circuit cards.

#### Available Options Include:

- **Computer interface:** RS-232, USB, etc. or complete data logging and acquisition systems.  
Output for Digital Printer

#### POWER:

- **Power:** 105-125 volts, 50-60 Hz (220 V optional)
- **Batteries:** 12v, 4.8 Amp Hour built-in L-ion battery pack with AC Charger Adapter
- **Battery Life:** 3-5 days at 8 Hour/day



**TECHNICAL ASSOCIATES**

Divisions of



US NUCLEAR CORP

**OVERHOFF TECHNOLOGY**

7051 Eton Ave., Canoga Park, CA 91303

818-883-7043 (Phone) 818-883-6103 (Fax)

[tagold@nwc.net](mailto:tagold@nwc.net)

[WWW.TECH-ASSOCIATES.COM](http://WWW.TECH-ASSOCIATES.COM)

# ANALYZING RATEMETER SCALER PORTABLE

**Model - LAM-SCA & LAM-10-DSC**

## **WEIGHT AND DIMENSIONS: - LAM-SCA**

- **Dimensions:** 10" L x 4.1"W x 7" H (25 cm L x 10.5 cm W x 18 cm H)  
Includes handle
- **Weight:** 5lbs (2.5kg) including batteries.
- **Options:** Alarm Relay

## **WEIGHT AND DIMENSIONS: - LAM-DSC**

- **Dimensions:** 10" L x 7" W x 7"H (25 cm L x 18 cm W x 18 cm H) Includes handle
- **Weight:** 8lbs (4kg) including batteries.

## **Over 50 Different T/A Probes And Sample Counter Detectors:**

### Some of TA's Detector Model Numbers

A	P6-LB		F	DMU-1000
B	PAS-9		G	P-15
C	BGS-IN		H	STB-TF-6
D	COLLIMATOR		I	TS-26
E	PLS-04		J	PN-3



**TECHNICAL ASSOCIATES**  
**OVERHOFF TECHNOLOGY**

7051 Eton Ave., Canoga Park, CA 91303  
818-883-7043 (Phone) 818-883-6103 (Fax)

[tagold@nwc.net](mailto:tagold@nwc.net)

[WWW.TECH-ASSOCIATES.COM](http://WWW.TECH-ASSOCIATES.COM)

Divisions of



US NUCLEAR CORP

# ANALYZING RATEMETER SCALER

## PORTABLE

### Model - LAM-SCA & LAM-10-DSC

#### RANGE SPECIFICATIONS:

Choose from a Sample of TA's Probe or Any TA or Compatible Probe.

PROBE	DESCRIPTION	RANGE						UNITS
<b>ALL PROBES</b>	<b>ALL PROBES</b>	<b>0.1</b>	<b>1</b>	<b>10</b>	<b>100</b>	<b>1,000</b>	<b>10,000</b>	<b>cps</b>
<b>GM</b>	Thin window Alpha-Beta, Gamma, X-ray							
<b>P-15</b>	2" dia Pancake		.02	.2	2	20	200	mR/h
<b>P6-LB</b>	Low Background		.1	1	10	100	1,000	mR/h
<b>SCINTILLATION</b>	<b>SCINTILLATION</b>							
<b>PGS-3T</b>	Low Energy Gamma			.01	.1	1	10	mR/h
<b>PGS-3I</b>	Low / Mid Energy Gamma			.03	.3	3	30	mR/h
<b>BGS-2505</b>	Low Energy BGO Probe			.01	.1	1	10	mR/h



**TECHNICAL ASSOCIATES**  
**OVERHOFF TECHNOLOGY**

7051 Eton Ave., Canoga Park, CA 91303  
818-883-7043 (Phone) 818-883-6103 (Fax)

[tagold@nwc.net](mailto:tagold@nwc.net)

[WWW.TECH-ASSOCIATES.COM](http://WWW.TECH-ASSOCIATES.COM)

Divisions of



US NUCLEAR CORP