



High Range Submersible Monitor

Model - CP-MU-10K

(Includes DMU-100 Probe to 10⁴R/hr)

Features

- Five Decades 0.1 to 10,000 R/hr.
- Waterproof Detector System
- Stable and Dependable
- Fast Response
- Lightweight and Portable
- 6-AA Cell
- 2-way Serial Port-standard
- Probe Cable 0-60 Ft
- Optional: 0.1 to 20,000 R/hr

Application


Extremely high range capability and waterproof construction of ion chamber detection system provides underwater monitoring and in hot cell monitoring of Reactor Spent Fuel Elements. Reactor components and dose rate measurements of irradiated objects can now be made easily and at the ranges called for.

General Description

- Lightweight single 6-AA cell operated, solid state and MOSFET driven electronic package.
- A High Range DMU-100 Detector System consisting of 60 feet of special low noise cable.
- A waterproof coupling to a 8" long x 1/2" diameter aluminum tube containing an ion chamber.
- A "handle" consisting of 8 foot sections of free draining 5/8" stainless steel tubing is available as an option.
- Five linear decades on the electronic package provide readings up to 10,000 R/hr. A "set" button on the front panel permits the meter to be adjusted to read zero by the zero adjust knob.
- Calibration is fully adjustable.
- The instrument case is made of drawn aluminum with epoxy lettering for easy decontamination. Case openings are sealed by gasket or screw closure for protection of electronics.
- A reliable MOSFET electrometer circuit and improved solid state electronics assure long uninterrupted service. Mechanical switching of the high impedance circuit has been eliminated.
- Protection against influence by magnetic fields up to 60 gauss has been built into the instrument. A top handle and four rubber feet achieve a more stable base with no loss of display visibility.



**TECHNICAL ASSOCIATES
OVERHOFF TECHNOLOGY**

DIVISIONS OF
 US NUCLEAR CORP

7051 ETON AVENUE, CANOGA PARK, CA 91303 | 818-883-7043 | F: 818-883-6103
RGOLDSTEINTA@USNUCLEARCORP.COM | TECH-ASSOCIATES.COM | USNUCLEARCORP.COM

High Range Submersible Monitor


Model - CP-MU-10K *(Includes DMU-100 Probe to 104R/hr)*

Specifications

Accuracy:	± 10% F.S.
Calibration:	Cs-137 Gamma (Co-60 Optional)
Time Constant:	2 seconds fast, 12 seconds slow
Drift:	At room temperature - less than 0.5% per °C
Battery:	6-AA Cells
Battery Check:	Push-button with LED indicator
Range Adjusts:	1 internal screwdriver adjust
Zero Adjust:	Knob
MOSFET:	Prevents damage to MOSFET when coupling or decoupling detector system
Serial Port:	RS-232 communications for data collection or remote computer readout
Dimensions:	6-1/2" long x 3-1/2" x 9" tall including handle
Weight:	Electronics 28 oz.
Detector System:	DMU-100 - Sealed Air ion chamber nominal 100cc volume
Readout:	LCD 8 digits
Indicator Lamp:	Green LED 1 pulse/sec R/hr. Red Over-range Indicator
Electrometer:	Solid State MOSFET input
Electronics:	A-D converter LCD drivers
Options:	Readout in Si units: Sv and Sv/h
Data Output:	WIN-W -- RS-232 Software
Options:	
Cable:	0-100 ft (30 meters)
Alarm:	Settable visual alarm LED
Range:	0.1 TO 20,000 R/hr
Non-Submersible Probe:	Lighter weight and optional wand/handle



**TECHNICAL ASSOCIATES
OVERHOFF TECHNOLOGY**

DIVISIONS OF
 US NUCLEAR CORP

7051 ETON AVENUE, CANOGA PARK, CA 91303 | 818-883-7043 | F: 818-883-6103
RGOLDSTEINTA@USNUCLEARCORP.COM | TECH-ASSOCIATES.COM | USNUCLEARCORP.COM