

Alpha Floor Monitor

Model: AFM-2

Detector Details:

- 4 PM tubes collect information from 144 sq. inches (925 cm) of zinc sulfide scintillators protected by thin light-tight easily replaceable window plus grille.
- 6" x 24" detector face; Window is less than 1 mg/cm.
- Sees Alphas rejects Gammas and Betas
- **Detector Type:** ZnS(Ag) for Alpha

Electronics: PUG-7-D

Digital Display:

Length = 6 digit rate, 8 digit total dose
Other meter scale markings are available.

Engineering Units:

User can input correct conversion factor and change to any units.

Front Panel Controls:

On-Off, Alarm-mute, Rate, Integrate, Alarm Set and Reset.

Recessed or Internal:

Discriminator level, high voltage

Other Adjustable Settings:

See calibration.

Detectors:

Any GM (P-13, P-15, P-6LB, etc.) or Alpha, Beta, Gamma or Neutron scintillator (PAS-8, PAS-9, PGS-3, PNS-19, etc.).

Input Sensitivity:

Adjustable from less than 1 millivolt to 100 millivolt

Accuracy:

±10%

Anti-Saturation and Dead-time Corrections:

Differentiation circuit provides highly effective compensation for coincidence loss. This allows all five decades to accurately read with scintillation detectors.

Calibration:

Digital input of calibration factor gives high precision adjustment.

Probe Connector:

BNC (optionally MHV) low noise Teflon insulated.

Battery:

9 volt battery (150-300 hours typical life).

Dimensions:

3-1/4" H, 4-1/4" W, 7-1/4" long excluding probe holder and handle.

Weight:

2 lbs. 4 oz.

Physical Features:

- Adjustable height above floor.
- Convenient handle,
- Weight 4 kg
- Three wheeled for ease of pivot ability
- Output for recorder.



TECHNICAL ASSOCIATES OVERHOFF TECHNOLOGY

7051 ETON AVENUE, CANOGA PARK, CALIFORNIA 91303

PHONE: 818-883-7043 | FAX: 818-883-6103

SALES@USNUCLEARCORP.COM | TECH-ASSOCIATES.COM | USNUCLEARCORP.COM

DIVISIONS OF



USNUCLEARCORP

OTCQB-UCLE