



TBM-3SR-D

Features

- Alpha, Beta-Gamma, X-Rays, Iodine
- Ideal for First Responders
- Real Time
- Portable
- Computer Interface
- Electronics – TBM-3SR-DD – **AIR-TBM-B**
 - » Battery Power
 - » Internal GM Pancake Detector
 - » **Optional:** Rechargeable Batteries with Charger
 - » **Optional:** Backlight
- AC Pump AP-5020E – **AIR-TBM-AC**
 - » AC Operation
 - » PGS-3 Probe
 - » Easy Change Filter'
 - » Flow Meter
 - » **Optional:** Battery Powered Pump
 - » No Flow Meter

Application

Quadruple Use:

- Air Monitor - Radiation
- Wipe Counter
- Surface Monitor
- Personal Air Sampler

Basic Radiation Air Monitor

Survey Meter, Wipe Counter, also Chem or Bio Aerosols

Model: AIR-TBM-AC and AIR-TBM-B



AIR-TBM-B
TBM-3SR-D with
Battery Pum
No Flow Meter



AC Pump, Hose
and Filter Holder

WH-15 Filter
and Holder

Description

The AIR-TBM uses standard 57-70 mm filters in TA's easy change, no leak filter, to trap any airborne radioactivity. The filter is under constant surveillance via pancake GM tube.

Air is drawn through the system by a continuous duty pump.

The unit is completely self-contained and portable. Room air is drawn in through the charcoal impregnated filter paper. Then through the pump and its 3 ft. exhaust hose that can be extended.

The AIR-TBM air sample filter holder from the AC pump can be connected to the TBM-3SR-D through a unique "groove and track" bracket on bottom of TBM-3SR-D. This provides attachment of the air sampler filter holder for read-out with the TBM-3SR-D. The TBM-3SR-D is itself a compact surface monitor and survey meter.



TECHNICAL ASSOCIATES OVERHOFF TECHNOLOGY

7051 ETON AVENUE, CANOGA PARK, CALIFORNIA 91303

PHONE: 818-883-7043 | FAX: 818-883-6103

SALES@USNUCLEARCORP.COM | TECH-ASSOCIATES.COM | USNUCLEARCORP.COM

DIVISIONS OF



USNUCLEARCORP

OTCQB-UCLF