## **Basic Radiation Air Monitor**

#### Survey Meter, Wipe Counter, also Chem or Bio Aerosols

#### Model - AIR-TBM

### Specifications

Measures: Airborne radioactivity including aerosol, particulate and gases excluding Noble Gases.

Sensitivity: Limit of sensitivity (99% confidence level) 1 nanoCi collected on filter paper.

TIME	SENSITIVITY	
1 Hour	3 x 10 <sup>-9</sup> µCi/cc	
24 Hours	1 x 10 <sup>-10</sup> µCi/cc	
5 Days	2 x 10 <sup>-11</sup> µCi/cc	

» 2 x 10<sup>-11</sup> μCi/cc after 5 days with pump running or 1 x 10<sup>-10</sup> μCi/cc after 24 hours

»  $3 \times 10^{-9} \mu \text{Ci/cc}$  after pump runs for 1 hour.

» This level is below 2/10th of the NRC Title 10 limit for 40 Hr. exposure to most hazardous Beta and/or Gamma emitter.

Detector: 2" diameter. Thin window 1-3/4" x 1.5-2 mg/cm² pancake T-1190 GM detector

Energy Range: 50KeV to 2 MeV

Accuracy: ±20%

Background: Typically 25 cpm

Flow Rate: Calibrated at factory. See chart below. Positive displacement pump

Filters: Pack of 50 filters, charcoal impregnated

Optional: Can use membrane, paper or glass fiber filters.

Case: Electronics housed in instrument-case, carrying handle included

Electronics: TBM-3SR-D Digital Ratemeter

Ranges: 0.01 to 100 mR/hr.

Meter Response Time: 2 seconds

Pump Power: AC 115V, 50-60 Hz (230 V Optional)

Optional: 6 AA batteries

Pump	Model#	Flow Rate	Weight
Battery Operated No Flow Meter	MINI-AIR-15	4ft <sup>3</sup> /hour (2 lpm)	1 <u>lb</u>
AC Operated	AP-5020E	0.5ft <sup>3</sup> /minute (15 lpm)	6 <u>lb</u>

## Weight and Dimensions

Dimensions TBM-3SR-D: 3" W x 5" H x 6" D
Weight TBM-3SR-D: Electronics – 1.5 lbs

Dimensions AC Pump: 5" W x 7" H x 10" L (Fold Down Handle)

Weight AC Pump: 6 lbs

Options: Inlet hose to allow monitoring of closed spaces. Rechargeable Batteries and Charger for TBM-3SR-D





# TECHNICAL ASSOCIATES OVERHOFF TECHNOLOGY

DIVISIONS OF

USNUCLEARCORP

OTCQB-UCLE

7051 ETON AVENUE, CANOGA PARK, CALIFORNIA 91303 PHONE: 818-883-7043 | FAX: 818-883-6103