



Tritium Air / Stack Monitor

For Public Release Level and Below

Model Series - H3-PRL

Model H3-PRL-5 - 5 Decade Concentration

Model H3-PRL-7 - 7 Decade Concentration

Application

Nuclear Power, Fusion Power, Bio-Tech Industry,
Environmental Monitoring, Indoor Air Quality

Features

- Ultra Sensitivity to Low Level Tritium
- 3×10^{-10} $\mu\text{Ci/cc}$ (10 Bq/m³ in 24 hrs)
- 5×10^{-9} $\mu\text{Ci/cc}$ (185 Bq/m³ 1 hr)
- 1×10^{-8} $\mu\text{Ci/cc}$ (370 Bq/m³ in 20 min)
- 1×10^{-7} $\mu\text{Ci/cc}$ (3.7K Bq/m³ in 3 sec)
- Stable - Self Contained
- RS-232, USB and Ethernet
- Gives Concentration
- Gives Total Daily Release
- Real-Time Alarm
- Dynamic Background Compensation
- Can Actuate Remote Control
- Particulate + Ion Inlet Filters
- Wall Mountable
- **Optional:** Measures Tritium as HTO in Presence of Other Radioactive Gases (STG-5ATL)

- » On Board Memory
- » Micro Processor to Establish Units And Parameters
- » USB and Ethernet Data Port
- » Digital Accuracy Sensitive to 10^{-7} $\mu\text{Ci/Cc}$
- » Measures Dose-Rate & Dose

Description

- H3-PRL Series Tritium monitors are sensitive, rugged stack or effluent monitors for detection and measurement of airborne Tritium.
- The subtractive balanced chamber electrometer circuit decreases background effects to negligible levels
- De-ionized and filtered intake reduces to negligible levels spuriousity based on smokes, dusts, and existing ionization in the air.
- Inlet and outlet hoses allow the return of monitored air to source: interiors of fume hoods, exhaust stacks, etc.
- Related models are available to selectively measure only airborne HT, or only HTO, or C-14, or exclude Ar⁴¹, Ra, etc.

- » Alarm – Visual and Audio
- » Dynamic Background Gamma Compensation
- » Can Actuate Computer or Remote Control
- » Measures Tritium as HTO In Presence of Other Radioactive Gases (STG-5ATL)
- » Cleans Gas Stream of Particulates and Ions



TECHNICAL ASSOCIATES OVERHOFF TECHNOLOGY

7051 ETON AVENUE, CANOGA PARK, CALIFORNIA 91303

PHONE: 818-883-7043 | FAX: 818-883-6103

SALES@USNUCLEARCORP.COM | TECH-ASSOCIATES.COM | USNUCLEARCORP.COM

DIVISIONS OF



USNUCLEARCORP

OTCQB-UCLE

Tritium Air / Stack Monitor

For Public Release Level and Below

Model Series - H3-PRL

Model H3-PRL-5 - 5 Decade Concentration | Model H3-PRL-7 - 7 Decade Concentration

Specifications

MODEL	ALL MODELS	H3-PRL-5	H3-PRL-7
	BOTTOM OF RANGE	TOP OF RANGE	TOP OF EXTENDED RANGE
RATE	$1 \times 10^{-7} \mu\text{Ci/cc}$	$1 \times 10^{-3} \mu\text{Ci/cc}$	$1.0 \mu\text{Ci/cc}$
	0.1 <u>picoCi/cc</u>	999.9 <u>picoCi/cc</u>	0.999 $\mu\text{Ci/cc}$
	3.7K <u>Bq/m³</u>	37M <u>Bq/m³</u>	37G <u>Bq/m³</u>

MODEL	H3-PRL		
	BOTTOM OF RANGE	TOP OF RANGE	INTEGRATION TIME
Integrate for Determining Concentration	3×10^{-10} (10 <u>Bq/m³</u>)	$1 \times 10^{-6} \mu\text{Ci/cc}$ (370 <u>Bq/m³</u>)	24 hours
	5×10^{-9} (185 <u>Bq/m³</u>)	$1 \times 10^{-5} \mu\text{Ci/cc}$ (3.7K <u>Bq/m³</u>)	1 hour
	1×10^{-8} (370 <u>Bq/m³</u>)	$1 \times 10^{-4} \mu\text{Ci/cc}$ (37K <u>Bq/m³</u>)	20 minutes

Integrate to Determine

- Total Daily RELEASE:** Model Series H3-PRL SERIES automatically multiplies real-time concentration by your average daily stack output and reports total daily release from 0 $\mu\text{Ci/day}$ to $1^{099} \mu\text{Ci/day}$.
- Background:** Essentially eliminated by subtractive balanced chambers.
- Smoke, Dust, Ion Elimination:** Filter and de-ionizer reduce effects to negligible levels.
- Circuit:** Electrometer circuit amplifies net difference between a 25 liter tritium internal chamber and internal background chamber of identical size and configuration.
- Detector:** Air stream is passed through sample chamber to measure all Tritium gas content.
OPTION: Xenon, Krypton, $^{14}\text{CO}_2$, etc.
- Calibration:** Can be calibrated internally with Tritium (or HTO) gas, or on a Gamma calibration course; or can be checked at a single point with an external (not provided) Beta source.
- Factory Calibration:** Performed prior to shipment with accompanying Calibration Certificate.
- Field Calibration:** Calibration check may be performed in the field with optional license exempt microCurie level Beta source.



**TECHNICAL ASSOCIATES
OVERHOFF TECHNOLOGY**

7051 ETON AVENUE, CANOGA PARK, CA 91303

P: 818-883-7043 | F: 818-883-6103 | C: 818-836-0381

SALES@USNUCLEARCORP.COM | TECH-ASSOCIATES.COM | USNUCLEARCORP.COM

DIVISIONS OF



USNUCLEARCORP

OTCQB-UCLC

Tritium Air / Stack Monitor

For Public Release Level and Below

Model Series - H3-PRL

Model H3-PRL-5 - 5 Decade Concentration | Model H3-PRL-7 - 7 Decade Concentration

Data Outputs

- Digital:** RS-232 serial port. One count per second per $1 \times 10^{-7} \mu\text{Ci/cc}$
- Analog:** **Optional:** 0-5 V or 4-20mA
- Alarms:** **High Level:** Red flashing light with audio
System Fault: White steady light
- Remote Alarm:** TTL closure for system failure
TTL closure for High Level alarm
- Data Retrieval:** RS-232 serial port
- Dimensions:** 36" W x 30" H x 17.5" D
- Weight:** 40 lbs. (18.4 kg)
- Optional Features/Accessories:**
- Remote alarm (audible and visual)
 - Model RAL[®] – Remote Alarm and Meter (including 25 ft of cable)
 - Can be used to 500'
 - 4-20 mA for computer
 - Other manual range switching or auto-range features
 - Relay contacts for high or low alarm, or both
 - Interconnection to/from port of other gas or particulate monitor
 - Readout as radioactive gas other than Tritium

TRITIUM SERIES COMPARISON ~ (PUBLIC RELEASE LEVEL OR LOWER)				
	MODEL	MODEL	MODEL	MODEL
	STG-4S/D	STG-5ATL	H3-PLR -5	H3-PLR -7
FEATURES	6 DECADES	4 DECADES	5 DECADES	7 DECADES
	H3 & NOBLE GASES	DETECTS HTO & H3	ALL TRITIUM	ALL TRITIUM
	$10^7 \times 10^{-3} \mu\text{Ci/cc}$	H3 - $10^7 \times 10^{-3} \mu\text{Ci/cc}$ HTO - $1 \times 10^{-7} \mu\text{Ci/cc}$	$1 \times 10^{-7} \mu\text{Ci/cc} - 1 \times 10^{-3} \mu\text{Ci/cc}$	$1 \times 10^{-7} \mu\text{Ci/cc} - 1.0 \mu\text{Ci/cc}$
	SINGLE CHAMBER	DUAL CHAMBER	DUAL CHAMBER	DUAL CHAMBER
	SEES ALL RADIATION ON (1) SINGLE CHANNEL	SEPARATELY ON (2) TWO CHANNELS	USES (1) SINGLE CHANNEL WITH RANGE SWITCHING	USES (1) SINGLE CHANNEL WITH RANGE SWITCHING
	DOSE & DOSE RATE	DOSE & DOSE RATE	READS: 3 SEC, 20 MIN, 1 HR, 24 HR, TOTAL DAILY RELEASE	READS: 3 SEC, 20 MIN, 1 HR, 24 HR, TOTAL DAILY RELEASE



**TECHNICAL ASSOCIATES
OVERHOFF TECHNOLOGY**

7051 ETON AVENUE, CANOGA PARK, CA 91303

P: 818-883-7043 | F: 818-883-6103 | C: 818-836-0381

SALES@USNUCLEARCORP.COM | TECH-ASSOCIATES.COM | USNUCLEARCORP.COM

DIVISIONS OF



USNUCLEARCORP

OTCQB-UCLC